





Capacitor Discharge Ignition system produces a hotter, more efficient spark at all engine speeds. It also helps reduce spark plug fouling.



**Exclusive Monoshock rear suspension** allows greater rear wheel travel. This long stroke helps keep the rear wheel on the ground for better control, more comfort, and consistent traction on road or off.

## DT125 WAMAHA

	<u> (M) TAMAHA</u>
ENGINE	
Туре	2-stroke single
Displacement	123 cc
Bore and Stroke	56 x 50 mm
Compression ratio	7.2 : 1
Maximum torque	1.36 kg-m (13.3 Nm)
	@6,500 rpm
Carburetion	(1) Mikuni VM22SS
Ignition	C. D. I.
Starting	Kick
Lubrication	Autolube
Transmission	6-speed
CHASSIS	
Overall length	2,080 mm
Overall width	865 mm
Overall height	1,130 mm
Seat height	835 mm
Wheelbase	1,350 mm
Ground clearance	265 mm
Dry weight	96 kg
Fuel tank capacity	6.8 ℓ
Oil tank capacity	0.9 ℓ
Suspension	and the second
Front	Telescopic forks
Rear	Monocross suspension
Brakes	
Front	Drum
Rear	Drum
Tires	
Front	2.75 x 21
Rear	3.50 x 18

Specifications subject to change without notice.