

YAMAHA'S TOUGH TWO-TIMER: THE DT125MX

The DT125MX looks a little like a motocrosser. And Yamaha offers no apologies. Years of competition have been ploughed back into the product: it's not surprising that it shows.

And yet the DT125 is more than ready for the street. The features that give it punch on the trail – the seven-port barrel, the Torque Induction system, the six-speed gearbox, the high-level exhaust (complete with expansion chamber), and the race-developed frame – are the very features that give it its peppy but easy handling character on the road.

The DT125 now boasts a moto-cross-style monoshock suspension system which not only provides greater wheel travel and superior damping but also, in conjunction with the sturdy triangulated swing arm, keeps the rear wheel in constant alignment to eliminate weave and wobble.

Fully equipped with lights, indicators, and instrumentation, the DT is stylishly at home on the street. What gives it the look of a motocrosser also gives it the comfort and maneuverability of a first-class roadster. (Induction) Yamaha's reed-valve Torque Induction utilizes variations in crankcase pressure to ensure accurate fuel intake. Crisper combustion and the elimination of blowback make for sharper, more even performance.

(Silencer) Gone are the days when exciting performance meant ripping noisily through the countryside. A built-in silencing system designed to comply with environmental requirements, meets the needs of all outdoor enthusiasts.

(Controls) Magura-style levers for smoother and easier control of clutch and brakes, with electrical switches placed for fingertip access.

(Instruments) Full instrumentation, including tachometer and trip meter, gently angled for easy reading and illuminated by soft green non-glare backlighting.

(Handlebars) Handlebar bracing tube for off-road use carries protective padding. (Emergency switch) Instantly reached from the throttle is the emergency stop switch, essential for off-road use and a valuable safety feature for street riding, (Transmissi transmissio carefully ch varying nee street. Mult straight-cut oil provide reliability.

125

Full street-legal lighting and instrumentation.

New leading-axle front forks.

ENDURO 125

stable Monoshock

423 aa, 2-stroke, single cylinder engine wili Autolube and Torque Induction.

YAMAHA

6-speed, close-ratio transmission.

www.legends-yamaha-enduros.com



DT125 SPECIFICATIONS ENGINE

DT125 SPECIFICATION	NS ENGINE
Туре	2-stroke
Tor	ue Induction Single
Displacement	
Bore & Stroke	56 × 50 mm
Compression ratio	
Max horsepower	
Max. lorgue	15.2 Nm (1.5 kg-m) @6.000 rev/min.
Lubrication system	Autolube
Starting system	Primary kick starter
Primary transmission	
Final transmission	
Gearbox	
Carburettor	
Clutch	
Battery	
Charging system	
Ignition type	

DIMENSIONS

Overall length 2.080 mm
Overall width
Overall height 1.120 mm
Wheelbase 1,350 mm
Ground clearance
Seat height 855 mm
Weight (net)
Fuel tank capacity 7 lit.
Oil capacity 0.9 lit.
Tyres. front 2.75-21-4PR
rear
Brakes, frontDrum
rearDrum
*Specifications subject to change without notice.



YAMAHA MOTOR N.V.

Postbus 7829 PROF. E.M. Meyerslaan 3 Amstelveen (Amsterdam), Holland