



Your introduction to the great sport of cross-country riding.

Meet the new Yamaha AT-1, an exciting 125cc trail machine that follows in the footsteps of Yamaha's unchallenged DT-1.

Lighter and easier to handle, the AT-1 is ideal for the rider who is just entering the fun-filled world of cross-country riding.

The heart of this machine is a newly developed aluminum single cylinder engine that features Yamaha's famed 5-port design. It is kept running cool and clean with the Autolube automatic oil injection system.

Rugged trail features include all of those proved best by the larger DT-1: special front forks that smooth out the roughest trail, rugged 5-speed transmission for power as you need it, separate tachometer and speedometer instruments.





NEW STANDARDS IN SAFETY

Sure-gripping trail tires, water and dust-proof brakes, and large head and tail lights are all standard.

RUGGED TRAIL FEATURES

These include a sturdy lightweight frame, special travel forks, engine guard, a maximum amount of ground clearance large non-slip seat, and separate tachometer and speedometer instruments.

5-PORT ENGINE

The additional port, in the aluminum single cylinder engine used by the AT-1, delivers an overall 10-percent increase in power.

Peak performance is assured by the Yamaha Autolube automatic lubrication system.



SPECIFICATIONS

PERFORMANCE Max. speed range Climbing ability	100-105 km h 62-65 mph 30 degrees
Min turning radius .	1.900 mm (74.8 in.)
Min. braking distance 14.8 m	@50 km h (58.3 ft, @31 mph

ENGINE
Type 2-stroke, 5-port. Single
Displacement 123 cc (7.51 cu. in.)

^{*} Specifications subject to change without notice.

Bore & Stroke	56 - 50 mm (2.205 - 1.969 in.)	
Compression ratio	7.1 1	
Max. horsepower	11.5 HP & 7,500 rpm	
Max. torque	1.17 kg m & 5 ft-lb (46,000 rpm	
Lubrication system	Autolube	
Starting system	Primary kick starter	
Transmission	5 speed gearbox	
DIMENSIONS		
Overall length	1.960 mm (77.2 in.	

Overall width	910 mm (35.8 in.
Overall height	1.090 mm (42.9 in.
Wheelbase	1.285 mm 50.6 in
Min. ground clearance	225 mm (8.9 in
WEIGHT (Net)	94 kgs. 207 lbs
FUEL TANK CAPACITY	7.2 lit. 19 US gal
OIL TANK CAPACITY	1.2 lit. 1 3 US qt
TIRES front	3.00-18-4 PI
rear	3.25-18-4P
WEIGHT Net FUEL TANK CAPACITY OIL TANK CAPACITY TIRES front	94 kgs. 207 lt 7 2 ltt. 1 9 US g 1.2 ltt. 1 3 US c 3.00-18-4

