

YAMAHA 250 SINGLE ENDURO



SINCE 1987

MODEL DT-1






YAMAHA 250 SINGLE ENDURO

This is a premier machine, destined for greatness... with more features experts desire than any rough-country motorcycle ever made.

Obviously, the new single cylinder Enduro is the ideal answer for the "single-minded" man who wants an all-purpose bike that's a bold step up from the other cycles in its class. A bike that can really take it. Standard features include Yamaha's exclusive 5-port engine design, automatic oil injection system, Yamaha's own Enduro-Travel Forks, separate tachometer and speedometer, detachable lights and spring-loaded foot pegs.

www.legends-yamaha-enduros.com



SPECIFICATIONS OF DT-1

PERFORMANCE

Maximum Speed Range — more than 70mph
 Climbing ability — 35 degree
 Min. turning radius — 1,920mm 75.6in
 Min. Braking distance — 40ft. @ 20mph

ENGINE

Lubricating system — Automatic oil injection system
 Bore & Stroke — 70x64mm
 Displacement — 246cc
 Compression ratio — 6.8:1
 Maximum horsepower 21/30 BHP* @ 7,000rpm
 Maximum torque 2.32m kg @ 5,000rpm (16.4ft. lbs)
 Transmission — 5-speed gear box
 Starting system — Primary coupled kick

DIMENSIONS

Overall length — 2,060mm 81.1in
 Overall width — 880mm 34.6in
 Overall height — 1,070mm 42.1in
 Wheelbase — 1,345mm 53.0in
 Min. Ground Clearance — 240mm 9.5in

WEIGHT, Net 108kgs 238 lbs.

FUEL TANK CAPACITY — 9.5lit. 2.5gal.

OIL TANK CAPACITY — 1.6lit. 1.6qt.

TIRES, Front — 3.25-19-4P.R.

Rear — 4.00-18-4P.R.

* WITH GVT KIT



SINCE 1887

YAMAHA INTERNATIONAL CORPORATION

P.O. Box 5040, Los Angeles, California 90054; Eastern Branch: No. 3 Yamaha Drive, Cherry Hill Industrial Center, Cherry Hill, N.J. 08034; Northwest Branch: 3000 S.E. Hawthorne, Portland, Oregon; M.E. West Branch: 1440 West North Ave., Milrose Park, Illinois / Canada: FRID, DEXLEY, Ltd., 804 West 5th Street, Vancouver 8, British Columbia, Canada