## A perfect off-road fun bike



Heavy-duty oil-damper rear shocks

Front and rear drum brakes

VXX100

## FEATURES

- 2-stroke single 97cc engine with red valve "Torque Induction" system ensures high, dependable power, and stable torque over a wide speed range.
- Front and rear drum brakes for smooth deteleration and sure stop in all riding conditions.
- Double-cradle tubular steel frame is lightweight yet rigid for increased steering capability.
- Heavy-duly oil-damper rear shocks provide consistent truction for better control and increased comfort.

- Lowered seat position increases stability and allows the rider to put his feet squarely on the ground.
- Headlight and taillight are standard outbrent.
- CDI system is reliable and virtually maintenance free.
- 5 speed transmission features well selected gear ratios for a wide range of applications both on and off the road.

## SPECIFICATIONS

| ENGINE                         |  |
|--------------------------------|--|
| Type 2-stroke, single          |  |
| Displacement                   |  |
| Bore & stroke                  |  |
| Compression ratio              |  |
| Max. power (DIN)               |  |
| @7,000 rpm                     |  |
| Max. torque (DIN)              |  |
| @6,500 rpm                     |  |
| Lubrication                    |  |
| CarburetionVM22SS              |  |
| Ignition                       |  |
| Starter system                 |  |
| Fuel tank capacity             |  |
| Oil capacity                   |  |
| Transmission                   |  |
| Final transmission Chain drive |  |

## yamahasenduros.com

| CHASSIS      |         |      |                            |
|--------------|---------|------|----------------------------|
| Overall leng | th      |      | 1,795 mm                   |
| Overall widt |         |      |                            |
| Overall beig | ht      |      | 960 mm                     |
| Seat height. |         |      | 730 mm                     |
| Wheelbase    |         |      | 1,190 mm                   |
|              |         |      | 200 mm                     |
| Dry weight   |         |      | 77 kg                      |
| Suspension   | (Front) | Tele | scopic forks               |
| Brakes       | (Kear)  |      | Swingarm                   |
|              | (Pront) |      | Drum                       |
| Tyres        | (Rear)  |      | Drum                       |
|              | (Rear)  |      | 2.50-18-4PR<br>3.00-16-4PR |