

YAMAHA

DT250D

YAMAHA TRAIL

YAMAHA



YAMAHA

It's a way of life.

www.legends-yamaha-enduros.com

Outstanding among real trail machines

Designed to respond to the touch whether traveling down the open road or bounding across rolling hills, the DT250D has several improvements over last year's model. The rear shock absorbing system utilizes the new "monocross" system to increase the possible vertical travel of the rear wheel, front forks with increased stroke, the air cleaner element installation position has been raised to prevent water from entering, the wheel rims, front and back, have been changed from steel to aluminum, the engine has been completely changed to give more power and lighter weight, and the overall handling of the bike is lighter and easier to handle.

Rider and machine safety can be seen in the dust- and waterproof brakes plus the rear flashers which are shock-mounted in rubber, and maintenance is easier with an easily-removable rear wheel.

In total, the DT250D is a better trail that will exceed your expectations.



DT250D

PERFORMANCE

Max. speed	124 km/h
Climbing ability	35 degrees
Min. turning radius	2,200 mm
Min. braking distance	15 m @ 50 km/h

ENGINE

Type	2-stroke, 7-port, Torque Induction® Single
Displacement	246 cc
Bore & Stroke	70 x 64 mm
Compression ratio	6.7-1
Max. torque	2.7 kg-m @ 5,000 rpm
Lubrication system	Autolube®
Starting system	Primary kick starter
Transmission	5-speed gearbox

DIMENSIONS

Overall length	2,185 mm
Overall width	870 mm
Overall height	1,165 mm
Wheelbase	1,420 mm
Min. ground clearance	255 mm

WEIGHT (Net)

	118 kgs
--	---------

FUEL TANK CAPACITY

	9 lit.
--	--------

OIL TANK CAPACITY

	1.1 lit.
--	----------

TIRES

Front	3.00-21-4PR
Rear	4.00-18-4PR

*Specifications subject to change without prior notice.