

AG100



AG100

FEATURES

- 2-stroke 97 cc single features reed-valve "Torque Induction" and delivers peppy power from very low rpms.
- A 5-speed transmission offers smooth, quick gear changes.
- Leading-axle front forks offer plenty of smooth wheel travel.
- Heavy-duty rear suspension with dual, preload-adjustable shock absorbers.
- Water- and mud-resistant drum brakes provide reliable stopping power.
- Fully electronic capacitor discharge ignition.
- Serrated footrests offer added convenience for work in muddy surfaces.
- Rugged tubular-steel guards protect the hand levers, headlamp, turn signals and crankcases from rocks and branches.
- Large, durable fenders with rubber flaps.
- Sturdy front and rear carriers come as standard equipment.
- Dual side stands offer added convenience.
- Knobby tyres provide strong traction.



Large, sturdy rear carrier



Convenient dual side stands

ENGINE

Type	2-stroke, single
Displacement	97 cc
Bore & stroke	52.0 x 45.6 mm
Compression ratio	6.6 : 1
Lubrication	Autolube
Carburation	VM20
Ignition	CDI
Starter system	Kick
Fuel tank capacity	11.0/
Oil tank capacity	1.5/
Transmission	5-speed
Final transmission	Chain drive

CHASSIS

Overall length	2,110 mm
Overall width	930 mm
Overall height	1,080 mm
Seat height	800 mm
Wheelbase	1,315 mm
Ground clearance	235 mm
Dry weight	99 kg

Suspension

Front	Telescopic forks
Rear	Swinging arm

Brakes

Front	Drum
Rear	Drum

Tyres

Front	2.75-19-4PR
Rear	3.50-18-4PR

Colouring	Ceramic Ivory, Sunshine Red
-----------	--------------------------------