

PW 50

- Responsive 49cc engine
- Automatic centrifugal clutch
- Capacitor Discharge Ignition (CDI)
- Smooth shaft drive



www.legends-yamaha-enduros.com

Photo: Original specification

FEATURES

- The 49cc, 2-stroke engine is quick and responsive for more riding fun.
- Automatic centrifugal clutch makes riding easy.
- Maintenance-free CD Ignition for smooth, even firing at all rpm's.
- The smooth and quiet shaft drive never needs to be adjusted.
- Front and rear brakes are both lever operated ... just like a bicycle's.
- 3-position starting switch increases safety by preventing accidental starts.
- The seat is deeply padded for added comfort and better control.
- Rubber handle protectors come as standard equipment ... another thoughtful touch from Yamaha.

www.legends-yamaha-enduros.com

SPECIFICATIONS

ENGINE

Type	2-stroke, single
Displacement	49 cc
Bore & stroke	40.0 x 39.2 mm
Compression ratio	6.0 : 1
Max. power (DIN)	2.7 PS (2.0 kW)/ 5,500 rpm
Max. torque (DIN)	0.39 kg·m (3.8 Nm)/ 4,500 rpm
Lubrication	Autolube
Carburetion	MIKUNI VW12
Ignition	CDI
Starter system	Kick
Fuel tank capacity	2 l
Oil tank capacity	0.3 l
Transmission	Automatic
Final transmission	Shaft drive

CHASSIS

Overall length	1,245 mm
Overall width	575 mm
Overall height	715 mm
Seat height	485 mm
Wheelbase	855 mm
Ground clearance	105 mm
Dry weight	37 kg
Suspension (Front)	Telescopic forks
(Rear)	Swing arm
Brakes (Front)	Drum
(Rear)	Drum
Tires (Front)	2.50-10 4PR
(Rear)	2.50-10 4PR