


FOR PLEASURE-SEEKERS ONLY...


With all the features that have made YAMAHA cycles first on the road, first in the field and first on the track, this brand-new cycle is again the leader....tops in its class!

The YA6 is a masterpiece of engineering achievement. It is the cycle that is destined to be the most talked-about cycle of the year. It has power. Power on the straightaway, power on the hills, power on the track. Its acceleration must really be seen to be appreciated. But power is only part of the story. The exclusive "Autolube" automatic lubrication system is the most welcome development for cyclists in years. New safety features, too, make this machine a pleasure to ride. And, speaking of pleasure, the smooth, quiet gearbox is the easiest to operate you've ever seen. The shock absorbers and other "comfort-plus" features assure the most enjoyable ride imaginable. But we can't tell it all here. We'd spoil the fun of your first ride. Make it soon!











AN EXCLUSIVE FIRST AUTOLUBE

A Yamaha exclusive....designed and engineered by and for Yamaha. The world's first motorcycle with this revolutionary feature. Forever eliminates pre-mixing gas and oil....exactly regulates the correct flow of fresh gas and oil. Keeps carburetor, engine, muffler and exhaust clean. Saves trouble, gives longer engine life, greater efficiency, less maintenance economical fuel and more consumption.

DYNAMIC START

A GIANT ON THE HILLS





SPECIFICATIONS PERFORMANCE

OF YA-6 Fuel consumption on paved flat road 154 mi/gal (65 km/1) Climbing ability 20° Min. turning radius 71.2 in. (1,900 mm)

(7 m at 35 km/h)

-						
	n	a	I D	e	×.	

Mode	a																													۵	
Type	1			î				ĵ.	1	*			1	1		ľ		1			Ť.		1		1			2	~	ve	i.
																											١,	ga		1	
Fuel																															
Lubrie	Ci	at	11	ŋ	9	S	Y	s	10	91		į,	•			2	•	9	P	8	1	 e	1	0	-	Ċ	su				
																														te	
Displa	a	C€	r	n	e	n	t				į.	÷		ę,	ç,	0		19		l	0		i,		1		+1	1	2	5 0	30

Bore & stroke	. 2.2 ×1.9 in (56 ×50 mm)
Compression ratio	
Max. horsepower	
Max. torque	. 2.8 lb/5.000 (1.25/5.000)
Starting method	Electric Starter & Kick
	Battery Ignition

DIMENSIONS

Overall length	76 8 in. (1,920 mm)
	29.0 in. (725 mm)
Overall height	41.8 in. (1,045 mm)
Wheel base	49.8 in. (1.245 mm)
Min. road clearance	
WEIGHT	264.5 lbs. (120 kgs)



Hamamatsu, Japan

Printed in Japan 41 5 + 30