

AG175



AG175

FEATURES

- 2-stroke 171 cc engine features reed-valve "Torque Induction" and produces responsive power over wide rpm ranges.
- Slick-shifting 5-speed transmission lets you make full use of engine power.
- Swinging arm rear suspension uses dual, preload-adjustable shock absorbers to provide plenty of traction over rough terrain.
- Sturdy front forks offer long wheel travel and a smooth, comfortable ride.
- Sealed front and rear drum brakes deliver reliable stopping power.
- Serrated footrests offer added convenience for work in muddy surfaces.
- Rugged steel-tube guards protect the hand levers, headlamp, turn signals and crankcases from rocks and branches.
- Dual side stands offer added convenience.
- Large front and rear fenders with rubber flaps keep mud and stones away from the rider.
- Electronic capacitor discharge ignition.
- Fully sealed drive chain and knobby tyres.



Lever guard/Clutch lock



Rugged skid plate

ENGINE

Type	2-stroke, single
Displacement	171 cc
Bore & stroke	66.0 x 50.0 mm
Compression ratio	6.5 : 1
Lubrication	Autolube
Carburetion	VM24SI1
Ignition	CDI
Starter system	Kick
Fuel tank capacity	11.0 l
Oil tank capacity	1.5 l
Transmission	5-speed
Final transmission	Chain drive

CHASSIS

Overall length	2,120 mm
Overall width	930 mm
Overall height	1,085 mm
Seat height	805 mm
Wheelbase	1,330 mm
Ground clearance	240 mm
Dry weight	106 kg
Suspension	
Front	Telescopic forks
Rear	Swinging arm
Brakes	
Front	Drum
Rear	Drum
Tyres	
Front	3.00-19-1PR
Rear	4.10-18-4PR
Colouring	Ceramic Ivory, Heat Red