

YAMAHA MR50



www.legends-yamaha-enduros.com

MR50. THE SMALL BIKE THAT TAKES YOU

A LONG WAY.

Don't let the size of the MR50 fool you. Because this remarkable new Yamaha is fully equipped with many "full-size" bike features. Items like Yamaha's sophisticated Monocross Suspension, developed originally for its racing machines. Monocross irons out the toughest bumps, and gives you tremendous off-road control.

The MR50 is also one of the most rugged bikes of its size ever built. It travels easily over any terrain with its powerful torque-induction two-stroke Yamaha engine. Plus, it's a dream in city traffic.

It size, it can be termed a "mini". But in terms of performance, there's maximum excitement for the beginner and the expert.

Performance. Low running costs. Power. You get it all with the MR50, the small trail bike that can take you a long way.

Low seat position and special arrangement of controls and handlebars makes the MR50 more comfortable to ride.

Monocross suspension gives you great traction and control off the road.



Capacitor discharge ignition (CDI) produces a hotter spark and reduces maintenance requirements.

The powerful 50 cc, torque-inducted, two-stroke engine is equipped with reed valve intake for better response over the entire power curve.

Autolube automatically regulates the oil-fuel mix for more power and improved durability.

Leading axle front forks have longer travel for better handling.

Primary kick starter for fast, easy starting in any gear.

MR50 ENGINE

Type 2-stroke, single
 Displacement 49 cc
 Bore and Stroke 40.0 x 39.7 mm
 Compression ratio 6.9 : 1
 Maximum power 6.0 PS (4.4 kW)
 @ 8,500 rpm
 Maximum torque 0.51 kg-m (4.99 Nm)
 @ 8,000 rpm
 Carburetion Mikuni VM16
 Ignition C.D.I.
 Starting Kick

SPECIFICATIONS

Lubrication Autolube
 Transmission 5-speed
CHASSIS
 Overall length 1,855 mm
 Overall width 770 mm
 Overall height 1,030 mm
 Seat height 740 mm
 Wheelbase 1,180 mm
 Ground clearance 210 mm
 Dry weight 71 kg
 Fuel tank capacity 6.5 l

Oil tank capacity 1.2 l
 Suspension
 Front Telescopic forks
 Rear Monocross suspension
 Brakes
 Front Drum
 Rear Drum
 Tyres
 Front 2.50-19-4PR
 Rear 3.00-16-4PR

**Because of our ongoing efforts to make Yamaha motorcycles even better, specifications are subject to change without notice.*



YAMAHA MOTOR CO., LTD.
 2500 SHINGAI WATA-SHI SHIZUOKA-KEN JAPAN

LIT-3MC-0103018-81E (BZ1) 56.4 x 10 Printed in Japan