



DT175MX

- Race developed 7-port torque induction engine
- O High top speed with low down pulling power
- O Motocross style monoshock frame
- O Adjustable gas/oil shock absorber
- Long travel forks
- O Cross-over expansion chamber exhaust system
- O High ground clearance duplex frame
- O Crankcase shield
- O Chain guide
- O Black contoured levers
- O Matt black engine for efficient heat dissipation

- O Lightweight half-width hubs ribbed for strength
- O High clearance plastic guards
- O Rubber mounted indicators
- O Braced, padded handlebars
- Engine kill button
- O Prop stand
- 6-speed gearbox
- O Electronic ignition
- O Competition screw on filter cap
- O Autolube lubrication
- Trail tyres

ENGINE

Type Cylinder Displacement Bore & Stroke Compression Ratio Maximum Horsepower Maximum Torque Lubrication System Starting Ignition Type Transmission

2 stroke Single 171cc 66×50mm 6.8:1 16.3hp 7000rpm 1.7kg-m 6000rpm Yamaha Autolube Primary kick CDI 6 speed

DIMENSIONS

Overall Length Overall Width Overall Height Wheelbase Ground Clearance Seat Height Weight Fuel Tank Capacity Oil Capacity Tyres-Front Rear

Brakes-Front

Rear

2080mm 885mm 1120mm 1350mm 265mm 855mm 99kg 7 litres 0.9 litres 2.75-21-4PR 3.50-18-4PR Drum

Drum